

# ABB drives for HVAC

## ACS320, 0.37 to 4 kW



The compact ACS320 will save energy throughout your pump and fan HVAC applications. From booster pumps, exhaust and condenser fans to supply and return fans, the drive's built-in HVAC features such as embedded BACnet (MS/TP) ensure easy and complete integration into building management systems.



Power and productivity  
for a better world™



## Making HVAC user friendly

The preprogrammed application macros and easy to use control panel make installation and drive setup simple. The control panel on the ACS320 uses HVAC terms and units, removing any guess work, and comes with 18 languages built-in. The unified height and depth of the drive frame sizes minimizes needed installation space.

## Energy savings

With energy savings of up to 70 percent, the ACS320 can help to attain sustainability targets. The drive's energy optimizer tunes the drive's performance to help save even more energy. Built-in energy efficiency calculators monitor the energy used and saved. The savings are shown in kilowatt-hours and in local currency. Carbon dioxide (CO<sub>2</sub>) emission reductions are also shown.

## Complete HVAC functionality

The ACS320 comes standard with four embedded communication protocols, including BACnet (MS/TP) for easy integration into building management

systems. Built-in real time clock and timers help you optimize energy use. The drive provides full output current at ambient temperatures of up to 50 °C without derating. Built-in software for controlling common HVAC applications includes:

- 2 PID controllers
- Timers with real time clock
- Pump and fan control
- Cooling fan control
- Pump cleaning
- Underload (broken belt) detection
- Pump protection
- Sleep function
- Pipe fill (precharge)

Typical applications for the ACS320 include:

- Supply and return fans
- Condenser fans
- Exhaust fans
- Fume hood fans
- Booster pumps
- Submersible pumps

## Easy to order

The drive can be ordered with the HVAC control panel, or can be ordered with the HVAC control panel and an EMC filter. These two packages simplify the ordering process.

## Advanced PC tool

The DriveWindow Light 2 PC tool can be used to monitor process performance or to set and tune drive parameters. It can also be used in offline mode to configure drive parameters before the drive installation on site.



## Technical data

<b>Supply connection</b>	
<b>Voltage and power range</b>	3-phase, 380 to 480 V ±10% (0.37 to 4 kW)
<b>Frequency</b>	48 to 63 Hz
<b>Connections</b>	
<b>Motor types</b>	Asynchronous induction motors
<b>Frequency</b>	0 to 500 Hz
<b>Switching frequency</b>	Selectable 4, 8, 12 and 16 kHz (derated)
<b>Type of control</b>	Scalar control and user definable U/f profiles Energy optimizer
<b>Inputs and outputs</b>	Two analog inputs, one analog output, five digital inputs (DI5 can be programmed for pulse train input), one digital output (can be programmed as pulse train output), one relay output.
<b>PTC and PT100</b>	Any of the 5 digital inputs or analog input can be configured for PTC. Analog output can be used to feed PT100 sensor.
<b>Communication</b>	Embedded fieldbus protocols: BACnet (MS/TP), Modbus RTU (EIA-485), Johnson Controls N2, Siemens Building Technology FLN (P1). Available as an external option: Ethernet adapter for remote monitoring.
<b>Options</b>	
<b>User interface</b>	HVAC control panel, ACH-CP-B Panel mounting kits for cabinet door installation
<b>I/O extensions</b>	MREL-01 module, three Form C relay outputs, 250 V AC/30 V DC
<b>Chokes and filters</b>	AC input and output chokes EMC filters
<b>PC tools</b>	DriveWindow Light 2
<b>Environmental limits</b>	
<b>Degree of protection</b>	IP20/optional NEMA 1 kit
<b>Ambient temperature</b>	-10 to +50 °C (+14 to +122 °F), no frost allowed
<b>Product compliance</b>	
<b>Directives and standards</b>	Low Voltage Directive 2006/95/EC, Machinery Directive 2006/42/EC, EMC Directive 2004/108/EC, CE and C-Tick approvals, UL, cUL and GOST R, RoHS compliant, Quality assurance system ISO 9001
<b>EMC</b>	Class C3 (2 <sup>nd</sup> environment unrestricted distribution) built-in as standard Class C2 and C1 with external optional EMC filters
<b>Vibration</b>	Seismic certification IBC-2003, 2006

For more information please contact your local ABB representative or visit:

[www.abb.com/drives](http://www.abb.com/drives)  
[www.abb.com/drivespartners](http://www.abb.com/drivespartners)

© Copyright 2012 ABB. All rights reserved  
Specifications subject to change without notice.